

M-G301-32

FEATURES



- ❖ Factory tested
- ❖ Polished Finish
- ❖ Available only as shown
- ❖ Safety Grab Bars
- ❖ Tub filler
- ❖ Whirlpool Body Jets
- ❖ Hand-held Shower
- ❖ Molded Seat – 17” High x 25” Wide
- ❖ Luxurious Head Rest Pillow
- ❖ Waterproof 16 ½” Walk-in Door
- ❖ Inline Heater
- ❖ Thermostatic Valve
- ❖ Inward Swinging Door
- ❖ Drain Access Panel
- ❖ Dual drain system
- ❖ Easy Installation (4-6 Hrs)
- ❖ Pressure Balance Valve (optional extra)
- ❖ Limited Life Time Warranty on the Door Seal

TECHNICAL INFORMATION

- **Materials:** Acrylic Composite
- **Power Supply:** 110V, 2.25KW
- **Dimensions:** 52 x 32 x 38 IN
- **Water Usage:** 50-55 Gallons
- **Dain capacity:** 40 gallons per minute

PLUMBING REQUIRMENTS

- Unit is equipped with flexible, metal braided ½ inch water supply hose with ½ female threaded connectors
- Need to install hot and cold shutoffs with ½ male threaded nipples (not included)
- 1) **2” drain** and 2nd) **2inch “toe tap” drain** with 90 degree angle for quicker draining
- **Note:** The flexible drain hose that is included with this unit is for installation into a floor drain only. Substituting the existing drain show for a different one will not void the warranty as long as there is no damage or evidence of misuse.

ELECTRICAL INFORMATION

- **Dedicated line** 10-2 wire with 110 volt, 30 amp GFCI breaker:
 - Water pump 110-120V 6.5 Amp
 - Inline heater 110-120 Volt 14 amp(pump and heater may have separate connections)

GENERAL INFORMATION

- **Note:** It is advised to have the tub onsite before preparing drain location.
- Unit must be leveled in its permanent position and all feet must be on the ground to fully support the tub. **Please check fittings for tightness before final connections.** Connections may have loosened during shipping. ***Manufacturer reserves the right to change specs or features at anytime. Please check to confirm details. 1-866-783-2661***

